

ROCIN-ECO -AUTOMATISIERTES LADEN

12. FORUM ELEKTROMOBILITÄT SCHLESWIG-HOLSTEIN


20.11.2024

MATTHIAS HARDT (AUDI AG)

Gefördert durch:







PROJECT INFORMATION



Project name	ROCIN-ECO
Poject duration	01.10.2021 – 30.06.2024 (30 months)
Project lead	IONITY GmbH
Project Partner	IONITY GmbH, AUDI AG, TÜV SÜD
Associated Partner	Porsche AG, BMW AG, Ford AG, AVL GmbH, Huber+Suhner AG, ROCSYS
Short description	ROCIN-ECO – Robot Charging Infrastructure Ecosystem enabling carefree emobility across Europe The goal of ROCIN-ECO is the development and demonstration of an interoperable, standardized, automated charging solution by means of a robot. Since the automated charging solution must be fully interoperable with both the charging infrastructure and e-vehicles, success can only be achieved with a coherent, integrated approach that involves standardization activities throughout the whole project. Our realization will be the only vendor-independent solution with a strong focus on non-discrimination and standardization. The practice-oriented approach by considering public use cases as well as a safe soft-robot technology and high charging performance confirm the difference of ROCIN-ECO from other projects. Respecting multiple aspects for automated charging we claim to find the optimal technology for enabling carefree emobility across Europe.

FUNDED PARTNERS



Gefördert durch:









ASSOCIATED PARTNERS & SUBCONTRACTORS


















+ offen für weitere Partner

ROCIN-ECO - INTRODUCTION






ROCIN-ECO - PROJECT GOALS



- 1. Understanding the ACDS process and technology
- 2. Provide recommendations towards standardization





Method

Get close to a standardizable process, with available means.

- 1. Choosing and Navigating to service site
- 2. Entering service site
- 3. Approaching and Parking at the automatic EVSE

4. Docking


- 5. Energy transfer
- 6. Undocking

7. Leaving the automatic EVSE




Method

Get close to a standardizable process, with available means.





First steps



Where are we now



Apr. 2022 Nov. 2023





Try out user stories and parking layouts



Test communications for a fully automated process



Jun. 2023

Installation of final demonstrator

Jun. 2022

Jan. 2023

Nov. 2023

Apr. 2022

Test physically plugging in and out.



Oct. 2022

Integrate infrastructure components

Simulate user story for the automated process




Test complete user story





Testing plugging in and out

- Provide demarcated parking spot
- Provide clearance between parking spot and arm






Try out user stories and parking layouts

- Front/reverse parking is most repeatable
- Only a noteworthy hazard while plugging in

Gefördert durch:









Integrate infrastructure components & Simulate user story for the automated process

- Charging process can remain as is (with Plug n Charge, or preauthorization)
- Pre-charge checks take the most time
- Parking based on ranging feedback is more difficult than parking based on lines





Test communications for a fully automated process

- Limited information exchange needed to execute process
- Most information exchange would take place in preparation of arrival

Gefördert durch:










Validate complete user story

- Setting up of BLE communication when coming in range is fast and reliable enough for ACDS
- UWB (CCC implementation): at least sufficient for confirming position pairing of EV-aEVSE, further investigation ongoing ...





ROCIN-ECO – THE FINAL DEMONSTRATOR



Demonstrate user story



EV actions

ACDS actions


Human

N/A

3. Approaching and 7. Leaving the Parking at the 5. Energy transfer 6. Undocking 4. Docking automatic EVSE automatic EVSE Open charge port Set up and control Start ACDS session Unlock connector Step in energy transfer cover Check ACDS Follow EV motions Trigger undocking Trigger docking Drive away compatibility Terminate ACDS Park EV Insert connector Extract connector session Close charge port Confirm correct Lock connector Pay Service parking cover Unblock drive train Disable drive train Step out

ROCIN-ECO – ACD STANDARDS IN PROGRESS





ROCIN-ECO - RECOMMENDATIONS TO STANDARDIZATION



EV requirements

- The EV can put its inlet it within the mating space.
- EV is off when the ACD is active
- It's the EV's responsibility to make the inlet accessible.
- Interlock mechanisms are only engaged when the ACD is not active

aEVSE requirements

- Safety for clamping hazard
- Inlet detection not depending on vehicle
- Charging process remains unchanged
- Follow passive vehicle motions
- Use of space standardizable, via physical parking features (marking/bumps/etc.)
- Provide a barrier crossing


Communication

- Direct communication and ranging via BLE/UWB via CCCv3, or indirect via backend
- Preparation via backend systems

ROCIN-ECO - CONCLUSIONS



- 1. Understanding the ACDS process and technology
- 2. Provide recommendations towards standardization





- 1. Choosing and Navigating to service site
- 2. Entering service site
- 3. Approaching and Parking at the automatic EVSE
- 4. Docking

5. Energy transfer

6. Undocking

7. Leaving the automatic EVSE



Thank you for your attention



Gefördert durch:



















